

ARE YOUR JANITORIAL CLOSETS IN COMPLIANCE WITH OSHA?

Janitorial closets and other building service areas have numerous opportunities for employee exposure to corrosive materials such as bleach, ammonium, chlorine, floor strippers and other hazardous cleaning agents. These cramped locations make it very difficult and expensive to install a wall mounted eyewash and as a result employees are often left unprotected.

MATERIAL SAFETY DATA SHEET

Sample Company
P.O. Box 1234
Anytown, NY 10001

GENERAL INFORMATION NUMBER: (800) 555-6789
EMERGENCY TELEPHONE NUMBER: (800) 555-3456
CHEMTEC: (800) 555-0000

REVISION DATE: November 11, 2004
DATE OF ISSUE: January 21, 2003

I - Product Identification

Title & Grant Cleaner

HAZARD IDENTIFICATION SYSTEM: HEALTH: 2 FLAMMABILITY: 0 REACTIVITY: 0
 HAZARD RATING: 4 - Extreme, 3 - High, 2 - Moderate, 1 - Slight, 0 - Insignificant

II - Hazardous Ingredients

INGREDIENT	APPROX.	OSHA	ACGIH	SPH 48 CFR	ELV	HM 121	122	CALF
Phosphoric Acid	20.0	3 mg/m ³	8 mg/m ³	Y	N	N	N	7664-10-2
Nonmetal	1.0	N/E	N/E	N	N	N	N	9010-43-9

III - Physical Data

BOILING POINT @ P: 212
 VAPOR PRESSURE @ 760 mm Hg: 500
 VAPOR DENSITY @ 760 mm Hg: 1.52
 SOLUBILITY IN WATER: Insoluble
 APPEARANCE AND ODOR: Pink liquid, cherry fragrance

IV - Health Hazard Data

EMERGENCY AND FIRST AID PROCEDURES IF IN EYES: Flush eyes and under eyelids with plenty of cool water for at least 15 minutes. Obtain immediate medical attention.

EMERGENCY AND FIRST AID PROCEDURES IF IN EYES: Flush eyes and under eyelids with plenty of cool water for at least 15 minutes. Obtain immediate medical attention.



OSHA 29 CFR 1910.151, Subpart k, section c “ Where the eyes or body of any person may be exposed to injurious corrosive materials, suitable facilities for quick, drenching or flushing of the eyes and body shall be provided within the work area for immediate emergency use.”



SEF-9000

The new Speakman SEF-9000 combination eyewash/service sink faucet adds important ANSI compliant protection to a janitorial closet. The eyewash is attached directly to the faucet and permits both units to operate independently. As a result only one plumbing connection is required and there is never a worry about delivering scalding water to the eyes. The unique design is equally beneficial for new installations as well as retrofits.

SPEAKMAN®

SPEAKMAN COMPANY
 P. O. Box 191 • Wilmington, DE 19899
 Phone: 1-800-537-2107 Fax: 1-800-977-2747
www.speakmancompany.com